



Laminar flow hood class III
Bio rad I-II

Features:

Microprocessor Controller displays all important information, centered and angled down for easy reach and viewing; fast and reliable operation. Long-life HEPA filters with 99.997% efficiency for particle size between 0.1 to 0.3 microns.

Adjustable time for uv control with 20 second delay for describes damage. The efficiency of 100% air filtered into the hood and 100% out of the lab. Body base, profile and plate material of electrostatic powder paint. Two valves on the body to enter and exit the gas (as requested). Two passes equipped with a UV lamp (case for equipment).

Fixed sash with 2 or 4 port gloves for more protection.

One-piece stainless steel tray (Seamless).

5 uv lamps (Philips made in Netherlands).

Low noise and ergonomic design.

Strong lighting (up to 1200 LUX).


2 gloves for more protection.

Three stages of filtration.

Vertical airflow system.

Strong centrifuge fan .

Two sockets.



	Product	model	Internal dimensions of cabin (mm)			External dimensions (mm)		
			length	width	height	length	width	height
1	Laminar flow class III	Bioraad-I	1230	672	690	1795	813	2150
2	Laminar flow class III	Bioraad-II	2060	672	690	2540	813	2150

SETTING UP BY RAAD TEBNOVIN ZIST PAYA Co.
DESIGN & MADE BY RAAD TEB NOVIN ZIST PAYA Co.
10YEARS After Sale Service & 1YEAR Garranty